

Linksys 1080p 3MP Outdoor Night Vision Bullet Camera



LCAB03VLNOD

Key Features

- Larger image sensor for better, cleaner images
- ePTZ functionality
- Motion detection
- Audio detection
- Wide dynamic range (WDR)*
- Privacy mask
- User management
- Profile management
- Event management
- Wide-angle viewing*
- Image cropping
- ONVIF-compliant v1.0 and v2.0
- Water-proof IP67-rated
- Vandal-resistant housing
- Multi-streaming
- True day/night with removable IR-cut filter
- Built-in SD/SDHC card slot for uninterrupted recording
- DI/DO for external sensor and alarm
- POE IEEE 802.3af-compliant
- Video Surveillance Manager software

* Via firmware upgrade

Protect your business and enhance your situational awareness with the Linksys 1080p 3MP Outdoor Night Vision Bullet Camera. Ideal for long-distance exterior visibility, these Linksys network cameras provide superior security, surveillance, and supervision.

- Large, 5MP sensor provides superior video quality.
- Night vision, motion detection, audio detection, and alarm/event notification help your business stay alert around the clock.
- Wide-angle view and wide dynamic range (WDR) available with a firmware upgrade.
- The IP67 weatherproof and vandal-resistant housing helps protect the system from both natural and criminal elements.
- Complies with Open Network Video Interface Forum (ONVIF) core specifications, versions 1.0 and 2.0.
- True day/night functionality with removable infrared-cut filter.
- Free Video Surveillance Manager software with user, profile, and event management capabilities.

Linksys 1080p 3MP Outdoor Night Vision Bullet Camera

Specifications

Imaging	
Sensor	5 Megapixel CMOS
Maximum Image Resolution	2048 x 1536, 3MP
Video	
Maximum Frame Rate	18 fps @ 2048 x 1536 30 fps @ 1920 x 1080 30 fps @ 1280 x 720
Image Compression	H.264/MJPEG/MPEG4
Bitrate Control	Variable Bitrate and Constant Bitrate
Lens	
Fixed/Vari-focal	Vari-focal Lens
Iris Control	Auto Iris
Focal Length	f = 3.3 ~ 10.5 mm
Focal Ratio	F1.4
Viewing Angle	Horizontal: 26° ~ 70° Vertical: 20° ~ 51°
Minimum Illumination	0 lux (IR On, B/W) 0.5 lux (IR Off, Color)
IR Illuminator	
Mechanical IR-Cut	Y
Infrared LED	24 pcs
Wavelength	850 nm
Distance (IR Distance)	25 m
Audio	
Compression	G.711/AMR
Audio Streaming	2-Way Audio
Audio Input	Y
Audio Output	Y
Compliance Information	
FCC/IC	FCC/IC Class A
CE	CE Class A
Water-Proof	IP67-Rated
Vandal-Proof	Vandal Resistant
Interface	
Ethernet	100Base-T
DI/DO	Y
SD/SDHC Card Slot	Y
Analog Video Out	Y
RS-485 for Scanners, Pan-tilts	Y
Power Supply	
Power over Ethernet	IEEE 802.3af
Maximum Power Consumption	< 7W
Environment	
Operating Temperature	-40°C ~ 50°C
Operating Humidity	10% to 80% Relative Humidity and Non-Condensing
Storage Temperature	-20°C to 60°C
Storage Humidity	5% to 90% Non-Condensing
Dimensions	
Unit Weight	1.10 kg

Learn more at Linksys.com/business