

Wireless Access Point Router with 4-Port Switch

Connect Your Wired and Wireless Networks to the Broadband Internet

Wired and Wireless
PCs with Broadband



Wireless Access Point Router
with 4-Port Switch
Model No.: BEFW11S4 ver. 2

Benefits

- Share Your Broadband Internet Access on Your Wireless and Ethernet Networks
- Economical—Share One IP Address in Your Home or Office
- Secure and Protect Your PCs from Intruders

Features

- Supports Universal Plug-and-Play for Easy Configuration
- Capable of up to 128-Bit WEP Encryption
- Supports Enhanced Security Using NAT Firewall, ZoneAlarm Pro*, and PC-cillin* Software
- Access Your Network Remotely Over the Internet through Virtual Private Networking (VPN)
- Supports IPSec and PPTP Pass-Through
- Administer and Upgrade the Router Remotely over the Internet
- Configurable as a DHCP Server on Your Network
- Advanced Security Management Functions for Port Filtering, MAC Address, Filtering, and DMZ Hosting
- Includes One Ethernet Cable to Connect to a Cable or DSL Modem
- Free Technical Support—24 Hours a Day, 7 Days a Week, Toll-Free US Calls
- 1-Year Limited Warranty

* Full versions can be downloaded and purchased separately.

Specifications

Model Number	BEFW11S4 ver. 2
Standards	IEEE 802.3 (10BaseT), IEEE 802.3u (100BaseTX), IEEE 802.11b (Wireless)
Protocol	CSMA/CD
Ports WAN LAN	One 10Base-T RJ-45 Port for Cable/DSL Modem Four 10/100 RJ-45 Switched Ports, One Shared Uplink Port
Speed	Router - 10Mbps, Switch - 10/100Mbps (Half Duplex) 20/200 (Full Duplex)
Cabling Type	UTP Category 5 or better
Operating Range (Wireless)	Indoors: 30 m (100 ft.) @ 11 Mbps 50 m (165 ft.) @ 5.5 Mbps 70 m (230 ft.) @ 2 Mbps 91 m (300 ft.) @ 1 Mbps Outdoors: 152 m (500 ft.) @ 11 Mbps 270 m (885 ft.) @ 5.5 Mbps 396 m (1300 ft.) @ 2 Mbps 457 m (1500 ft.) @ 1 Mbps
LEDs WAN LAN	Power Diag, Act, Link 100, Full/Col, Link/Act Power, WLAN Link, WLAN Act
Warranty	1-Year Limited

Environmental

Dimensions	7.31" x 6.16" x 2.44" (186 mm x 154 mm x 62 mm)
Unit Weight	19.2 oz. (0.56 kg)
Power	External, 5V DC, 2.5 A
Certifications	FCC, CE, VCCI, UL, WiFi
Operating Temp	0°C to 40°C (32°F to 104°F)
Storage Temp	-20°C to 70°C (-4°F to 158°F)
Operating Humidity	10% to 85%, Non-Condensing
Storage Humidity	5% to 90%, Non-Condensing

Package Contents

Wireless Access Point Router with 4-Port Switch

- One Wireless Access Point Router with 4-Port Switch
- Two Detachable Antennas
- One Setup Wizard CD-ROM with User Guide Included
- One Power Adapter
- One CAT 5 UTP Cable
- One Fast Start Guide and One Registration Card

Linksys

17401 Armstrong Ave.
Irvine, CA 92614 USA

Sales Information (800) 546-5797

World Wide Web* <http://www.linksys.com>

Japan (03) 5259-5137

Philippines (632) 638-5580

Singapore 552-8998

Thailand 717-0770

United Kingdom 0870 7393939

*Visit our website for the most current contact information.