

10/100Mbps Fast Ethernet Performance in a PCI Card for Desktop Computers



Built to run with the fastest video, publishing, and database network applications, the EtherFast® 10/100 LAN Card is a high performance network adapter for 32-Bit PCI local bus computers. Boasting an incredible maximum data throughput of 200 megabits-per-second in full duplex mode, it includes a dual-speed 10BaseT/100BaseTX port, which means that you can begin integrating Fast Ethernet now, even if you don't plan on upgrading to a 100Mbps network right away.

The EtherFast® 10/100 LAN Card is Windows Plug-and-Play compatible and also runs on most popular OSes, including Windows 95, Windows 98, Windows ME, Windows NT, Windows 2000, and Windows XP. Wake-On-LAN support is built in—you can wake up your workstations from anywhere on the network! Built-in support for the widest range of PCI motherboards, networking hardware, and software means that you don't have to worry about compatibility.

Easy to Use Plug-and-Play 10/100 PCI LAN Card

Full Duplex Transfer Rate Capability of Up To 200Mbps

Connects to Both 10Mbps Ethernet and 100Mbps Fast Ethernet Networks

Power On Your PC From Anywhere on the Network with Wake-On-LAN Management

EtherFast® **10/100** LAN Card

Product Data



EtherFast® 10/100 LAN Card

Features

- Superb Fast Ethernet Performance in a LAN Card
- 10BaseT and 100BaseTX Fast Ethernet for PCI Local Bus PCI-Equipped PCs
- Includes Auto-Detecting 10BaseT/100BaseTX RJ-45
- Port that Automatically Adjusts to Full or Half-Duplex
- Wake-On-LAN and Plug-and-Play Compatible
- Easy to Install and Use
- Runs with Windows 95, 98, ME, NT, 2000, and XP
- Bus Mastering 32-Bit Architecture
- Diagnostic LEDs for Easy Troubleshooting
- Boot ROM Socket for Optional Remote Boot ROM with PXE Support
- Free 24-Hour Technical Support in North America Only
- Limited Lifetime Warranty

Specifications

Model No.	LNE100TX v5.1
Standards	IEEE 802.3, IEEE 802.3u, PCI 2.1, ACPI, PC99
Protocol	CSMA/CD
Ports	One 10BaseT/100BaseTX RJ-45 Port
Cabling Type	UTP Category 5 or better
Speed	Full Duplex: 20Mbps or 200Mbps Half-Duplex: 10Mbps or 100Mbps
WOL Support	Power Management Event (PME)
Bus Type	32-Bit PCI
LEDs	Link/Activity, 100Mbps
Sockets	One Boot ROM Socket

Environmental

Dimensions (W x H x D)	4.8" x 4.75" X .75" (122 mm x 121 mm x 19 mm)
Unit Weight	1.6 oz. (0.05 kg)
Power Input	5W Maximum
Certifications	FCC Class B, CE Mark Commercial
Operating Temp.	32°F to 122°F (0°C to 50°C)
Storage Temp.	-4°F to 158°F (-20°C to 70°C)
Operating Humidity	10% to 90%, Non-Condensing
Storage Humidity	5% to 95%, Non-Condensing

Linksys
A Division of Cisco Systems, Inc.
18582 Teller Avenue
Irvine, CA 92612 USA

E-mail: sales@linksys.com
support@linksys.com

Web: <http://www.linksys.com>

Linksys products are available in more than 50 countries, supported by 12 Linksys Regional Offices throughout the world. For a complete list of local Linksys Sales and Technical Support contacts, visit our Worldwide Web Site at www.linksys.com.

Minimum Requirements

- 200 Mhz or Faster Processor
- 64 MB of RAM
- Available PCI Slot
- CD-ROM Drive
- Windows 95, 98SE, Me, NT 4.0, 2000 or XP

Package Contents Head

- One EtherFast® 10/100 LAN Card
- One Driver Disk
- One User Guide and Registration Card

Specifications are subject to change without notice. Linksys is a registered trademark or trademark of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries. Copyright © 2003 Cisco Systems, Inc. All rights reserved. Other brands and product names are trademarks or registered trademarks of their respective holders.